

PRELIMINARY PRODUCT INFORMATION

EB-L1000U Series

Key features

- Laser light source with 20,000hrs light source life expectancy in standard mode and up to 56,000hrs in constant brightness mode¹
- Powered lens with lens memory
- New UST lens (<0.35:1)
- Full lens coverage from 0.65:1 to approx. 10.12:1
- Integrated camera for automatic image correction over lifetime
- Total 360° installation (side to side and nose to tail) with no loss of brightness
- Split screen including two digital inputs



Product specifications

		Resolution	Brightness (lumens)	Panel size (inches)	4K enhancement	Lens shift	Lens memory	3G-SDI ²	DMX Art-net	Speaker	Size (mm) WxDxH	Weight (Kg)	Colour	
Standard	EB-L1100U	WUXGA	6,000	3 x 0.76"	Yes	Motorised V: ±67%, H: ±30%	Yes	No	No	1 x 10W	586 x 492 x 185	21	White	
	EB-L1200U		7,000										Black	
	EB-L1300U		8,000										White	
Pro	EB-L1405U		8,000	3 x 1.03"		Motorised V: ±60%, H: ±18%		Yes	Yes	Yes		No	22	Black
	EB-L1500U		12,000											White
	EB-L1505U		12,000											Black

Lens specifications

		ELPLX01	ELPLU03	ELPLU04	ELPLW05	ELPLW06	ELPLM08	ELPLM09	ELPLM10	ELPLM11	ELPLL08
EB-L1100U	Throw ratio	0.35:1	0.65-0.78:1	0.87-1.06:1	1.04-1.46:1	-	1.45-2.32:1	2.15-3.49:1	3.31-5.07:1	4.84-7.39:1	7.2-10.12:1
EB-L1200U	Lens shift	V: ±17% H: ±10%	V: ±67% H: ±30%	V: ±67% H: ±30%	V: ±67% H: ±30%	-	V: ±67% H: ±30%	V: ±67% H: ±30%	V: ±67% H: ±30%	V: ±67% H: ±30%	V: ±67% H: ±30%
EB-L1300U	Throw ratio	-	0.48-0.57:1	0.64-0.78:1	0.76-1.07:1	1.19-1.63:1	-	1.58-2.56:1	2.43-3.71:1	3.54-5.41:1	5.28-7.72:1
EB-L1405U	Lens shift	-	V: ±24%, H: ±10%	V: ±60%, H: ±18%	V: ±24%, H: ±10%	V: ±60%, H: ±18%	-	V: ±60%, H: ±18%	V: ±60%, H: ±18%	V: ±60%, H: ±18%	V: ±60%, H: ±18%
EB-L1500U	Throw ratio	-	0.48-0.57:1	0.64-0.78:1	0.76-1.07:1	1.19-1.63:1	-	1.58-2.56:1	2.43-3.71:1	3.54-5.41:1	5.28-7.72:1
EB-L1505U	Lens shift	-	V: ±24%, H: ±10%	V: ±60%, H: ±18%	V: ±24%, H: ±10%	V: ±60%, H: ±18%	-	V: ±60%, H: ±18%	V: ±60%, H: ±18%	V: ±60%, H: ±18%	V: ±60%, H: ±18%
F No.		TBC	2.0-2.26	2.0-2.1	2.0-2.23	1.8-2.26	1.65-2.27	1.8-2.51	1.81-2.4	1.81-2.34	1.8-2.45

¹ At 30% brightness (TBC) ² Does not support 4:4:4 sampling
Product information is subject to change without prior notice.