

# HERMAinkprint gloss (211)

## White cast-coated glossy inkjet paper

### Specifications

Grammage		[g/m <sup>2</sup> ]	approx. 86	ISO 536
Caliper		[μm]	approx. 102	ISO 534
Tensile strength	MD	[N/15 mm]	approx. 80	DIN 53112
Tensile strength	CD	[N/15 mm]	approx. 40	DIN 53112
Stiffness	MD	[mN]	approx. 210	DIN 53121
Stiffness	CD	[mN]	approx. 130	DIN 53121
Opacity		[%]	approx. 87	ISO 2471

### Self-adhesive compound

**211 / 62G / 523**

label paper	86 g / m <sup>2</sup>
adhesive	17 g / m <sup>2</sup>
backing paper	59 g / m <sup>2</sup>
total grammage	approx. 162 g / m <sup>2</sup>

### Applications and use

With its special coat, the glossy surface of the HERMAinkprint gloss is particularly suitable for inkjet printers (waterbased dye-inks and pigmented inks).

Thanks to its specially designed surface characteristics an outstanding quality of the imprint is achieved on all usual inkjet printers (Canon, Epson, HP etc.) both in sheet-fed and continuous printing. It is also well suited to the Memjet-technology.

### Regulations concerning contact with food

The inkjet paper grade HERMAinkprint gloss (Grade 211) according to the sample material submitted is physiologically and toxicologically safe and may therefore be used in printers and scales for the marking of goods. However it may only have direct contact to foodstuffs which are washed and/or peeled before consumption (ISEGA Research and Development Institute, Aschaffenburg).

All statements, technical information and recommendations regarding HERMA products are given in good faith and are based on tests that we believe to be reliable, but do not constitute a guarantee or warranty.

We give no guarantee as to the suitability of the product for a specific application, this should be tested by the user.

Unless otherwise agreed in writing, we only accept liability within the scope of our General Terms and Conditions of Delivery and Payment.