

Technical Data Sheet

Ink-Jet Media specification Typical Values

NAK Gloss White PET Ink-Jet Label

Material code: PEWG

Face Material characteristics:

Glossy Ink-Jet coated Polyester-Film (PET) with good absorption characteristics, vibrant color print-out on dye based and some pigmented inks. Test printouts recommended.

Parameter	Value	Unit	Standard
Basic weight	79 ± 5	g/m2	ISO 536
Paper thickness	102 ± 5	µm	ISO 534
Opacity	➤ 87	%	ISO 2471
Stiffness md	➤ 30	mN	DIN 53 121
Stiffness cd	➤ 35	mN	15° / 10 mm

Adhesive characteristics:

This adhesive is a permanent adhesive, high adhesion, universal useable,

Parameter	Value	Unit	test method
	from / to		
Temperature range:	-20°C	+80°C	climate Chamber / Kofler bank
Labelling temperature	min.	+5°C	on glass

Backing characteristics:

Kraft liner white

Parameter	Value	Unit	Standard
Basic weight	62 ± 6	g/m2	ISO 536
Paper thickness	51 ± 5	µm	ISO 534

Testing beforehand is always recommended.

All data to be considered as typical values and subject to change without prior notice.

For any inquiry or comment, please contact us via e-mail to salesupport@nakagawa.de

Rev.053117