

**ARTICLE:****PS1627**

Polyester satin, non fray

DESCRIPTION

Optical white, opaque pré-coated, high density polyester satin, non-fray. Suitable for waterbased-high speed inkjetprinting.

PHYSICAL CHARACTERISTICS

<u>Warp:</u>	75 yarn/ cm
<u>Weft:</u>	150 yarn/ cm
<u>Total weight:</u>	170 g/m ²
<u>Total thickness:</u>	180 micron

AVAILABILITY:Jumborolls:Tape:Sheets:

Net Width (mm)

1450

1420

1400

COLOURS:

Optical white

WASHING PROPERTIES:

-

PRINTING:

Suitable for waterbased-inkjetprinting (high speed).

APPLICATIONS AND USERS:

Sew on matrrass lables

**RECOMMENDED STORAGE
CONDITIONS:**

18-23°C, 50-55% RH, avoid UV exposure.

APPLICATION CONDITIONS:

-

REMARKS:

It is advised to do preliminary printing trials to evaluate the water resistance of the printed media.

For optimal lasting quality prints made with dye based inks, frequent and/or long long lasting exposure to high humidity levels (e.g. above 75% RH) should be avoided if possible.

SHELF LIFE:

1 year in original packaging

This datasheet contains proprietary information of emax holding. Any reproduction, distribution or sales in any form of the content is prohibited. All statements, technical information and recommendations are based upon tests believed to be reliable but do not constitute a warranty. Emax products are warranted to the original purchaser to be free from defects in material or workmanship for a period of one year from date of shipment. Emax specifically disclaims and excludes all other such warranties, in no event shall emax be liable to purchaser or any other party for indirect, consequential, incidental, special or punitive damages.