



Label solutions

**ARTICLE:**

**FPPN1500**

Matt polypropylene

**DESCRIPTION**

White, polypropylene with matt coating, one side. Suitable for high speed inkjet.

**PHYSICAL CHARACTERISTICS**

<u>Warp:</u>	- yarn/ cm
<u>Weft:</u>	- yarn/ cm
<u>Total weight:</u>	104 g/m <sup>2</sup>
<u>Total thickness:</u>	180 micron

**AVAILABILITY:**

Net Width (mm)

**Jumborolls:**

1020

**Tape:**

1000

**Sheets:**

1000

**COLOURS:**

White

**WASHING PROPERTIES:**

n.a

**PRINTING:**

Suitable for dye and pigment ink in high speed inkjet systems.

**APPLICATIONS AND USERS:**

Hang tag syntetic label for indoor and outdoor usage.

**RECOMMENDED STORAGE  
CONDITIONS:**

18-23°C, 50-55% RH, avoid UV exposure.

**APPLICATION CONDITIONS:**

It is advised to do preliminary printing trials, to evaluate the water resistance and to test the compatibility with pigment based inks. For optimal lasting quality prints made with dye based inks, frequent and/or long long lasting exposure to high humidity levels (e.g. above 75% RH) should be avoided if possible.

**REMARKS:**

-

**SHELF LIFE:**

1 year in original packaging

*This datasheet contains proprietary information of emax holding. Any reproduction, distribution or sales in any form of the content is prohibited. All statements, technical information and recommendations are based upon tests believed to be reliable but do not constitute a warranty. Emax products are warranted to the original purchaser to be free from defects in material or workmanship for a period of one year from date of shipment. Emax specifically disclaims and excludes all other such warranties, in no event shall emax be liable to purchaser or any other party for indirect, consequential, incidental, special or punitive damages.*