

ARTICLE:
PGS1516G065

Embossed paper selfadhesive.

DESCRIPTION:

White, embossed paper selfadhesive. Suitable for high speed inkjet printing.


PHYSICAL CHARACTERISTICS:

Warp: - yarn/ cm
Weft: - yarn/ cm
Total weight: 208 g/m²
Total thickness: 225 micron

ADHESIVE:

Permanent hotmelt adhesive.

Properties: Initail high tack. Excellent adhesion over different polar and non polar surfaces.

Adhesive strength:

LINER:

Glassine yellow release paper, Suitable for fotocell guided processes.

Weight: 65 g/m² (+/-5%)
Caliper: 55 micron (+/-5%)

AVAILABILITY:

Net Width (mm)

Jumborolls:

1350

Tape:

1320

Sheets:

n.a

COLOURS:

White

PRINTING:

Suitable for dye and pigment ink in high speed inkjet systems.

APPLICATIONS AND USERS:

Packaging and labeling of boxes, bottles etc, to high light natural and handmade products.

RECOMMENDED STORAGE CONDITIONS:

18-23°C, 50-55% RH, avoid UV exposure, avoid close exposure to heatsources, keep from freezing, do not stack higher than 50 cm.

APPLICATION CONDITIONS:

Apply on dry, clean (e.g. no dust, oil, etc.) surfaces.
 Minimum application temperature: +5°C
 Service temperature: -20°C to 70°C

REMARKS:

It is advised to do preliminary printing trials, to evaluate the water resistance and to test the compatibility with pigment based inks. For optimal lasting quality prints made with dye based inks, frequent and/or long long lasting exposure to high humidity levels (e.g. above 75% RH) should be avoided if possible.

SHELF LIFE:

1 year in original packaging